

Eltex® Superstress™ CAP602S2

Product Technical Information

Eltex® Superstress™ CAP602S2 is a high-density polyethylene copolymer manufactured by INEOS Polyolefins using its proprietary supported catalyst & process particularly intended for the injection moulding of screw caps for the packaging of beverages. It is especially suitable for applications requiring outstanding environmental stress cracking resistance and thanks to high purity and excellent organoleptic properties, particularly intended for packaging in direct contact with beverages.

Typical applications

- Injection of caps & closures for the packaging of carbonated soft drinks
- Use in warm regions & cases, where ESCR can be a problem with standard grades
- Possibility to reach new designs with reduced cap weight

Benefits and Features

- Outstanding stress cracking resistance
- Good processing performances
- Very high impact strength
- Excellent, quality controlled organoleptic properties. In order to preserve the excellent organoleptic properties, it is important not to exceed a melt temperature of 250°C during processing.
- Grade containing slip agent ensuring easy application and opening
Exposure to direct sunlight has to be avoided as the slip agent is light sensitive and its degradation can give off-taste to the beverage.

Properties		Test Methods	Values	Units
Physical				
Density		ISO 1872	953	kg/m ³
Melt Flow Rate	2.16 kg load	ISO 1133	0.8	g/10min
Mechanical				
Tensile Modulus		ISO 527 -1&2 (1B)	1200	MPa
Tensile Strength	@ Yield	ISO 527 -1&2 (1B)	26	MPa
Charpy Impact Strength, 23°C		ISO 179	9.0	kJ/m ²
Environmental Stress Cracking Resistance (ESCR)		INEOS	> 40	h
Other				
Organoleptic properties		INEOS	OK	-

The values given are typical values measured on the product. These values should not be considered as specification



Eltex® Superstress™ CAP602S2

The high performance HDPE product, produced with INEOS proprietary leading edge processes, is protected by some or all of the following patents and patents applications: EP603935B, EP134971A, EP1420046A, EP1482008A, EP1544244A, WO03/039984A; EP1441959A, EP1462378A, EP1468932A and EP1278797B.

Storage

Eltex® Superstress™ CAP602S2 should be stored in a dry dust free environment, away from direct sunlight exposure and at temperature below 45°C.

Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, send an email to psnohreg@innovene.com. Unless specifically indicated, the products mentioned herein are not suitable for applications in the medical or pharmaceutical sector.

Health and Safety Information

The product described herein may require precautions in handling. The available product health and safety information for this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained from the website <http://techservice.innovene.com>. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

Exclusion of Liability

Although INEOS POLYOLEFINS endeavours to ensure that all information and advice relating to our materials or other materials howsoever provided to you by INEOS POLYOLEFINS is accurate and up to date, no representation or warranty, express or implied is made by INEOS POLYOLEFINS as to its accuracy or completeness. All such information and advice is provided in good faith and INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action you may take as a result of relying on such information or advice or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

In addition data and numerical results howsoever provided to you by INEOS POLYOLEFINS are given in good faith and are general in nature. Data and numerical results are not and shall not be regarded as specifications and as such INEOS POLYOLEFINS is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such data and results or for any loss or damage, including any consequential loss, suffered by you as a result of taking such action.

It remains at all times your responsibility to ensure that INEOS POLYOLEFINS materials are suitable for the particular purpose intended and INEOS POLYOLEFINS shall not be responsible for any loss or damage caused by misuse of INEOS POLYOLEFINS products. To the maximum extent permitted by law, INEOS POLYOLEFINS accepts no liability whatsoever arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu of INEOS POLYOLEFINS materials or the use of INEOS POLYOLEFINS materials in conjunction with such other materials.