



Masterbatches e Additivi per Materie Plastiche ed Elastomeri

FERRO-PLAST S.r.l.

Via Grandi, 25 - 20090 Vimodrone (Mi)

Tel. +39.02.27409415 Fax +39.02.27409420 E-mail ferroplast@ferroplast.com - www.ferroplast.com

FerroBlack ABS-1539 R

Informazioni Tecniche

FerroBlack ABS-1539 R is a black concentrate with high heat stability for the coloring of a wide range of polymers.

Composition

FerroBlack ABS-1539 R Masterbatch contains Carbon Black and Recycle ABS.

Technical Data

| | | |
|----------------------------|---|----------------------|
| Base Resin | : | Recycle ABS |
| Specific Gravity (TS1310) | : | - gr/cm ³ |
| Light Fastness | : | 8 |
| Heat Resistance | : | 300 °C |
| Total Carbon Black Content | : | % 35 |
| Carbon Black Type | : | HAF |

Application

FerroBlack ABS-1539 R can be used for the colouring of injection and extrusion applications. It is recommended an addition of 1 to 5 % depending on the requested colour intensity.

Packaging and Storage

FerroBlack ABS-1539 R is supplied in 25 Kg Polyethylene Valve Bags.
The Storage should not exceed 12 months.

If the masterbatch is stored below 40°C in a dry and dark places far from heat sources and direct sunlight , It has a usable life of 24 months from the date of production.

Hazard properties

It is not included in any dangerous material and any kinds of risk is not expected because of pigments are coated with base resin ABS