HOSTAFORM® FK 1:25 - POM

Description

acetal color masterbatch/concentrate
Hostaform® FK color masterbatches (color concentrates) are for use with other acetal products based in Celanese's acetal copolymer. Hostaform® FK color masterbatches are specially designed to provided color to other Celcon® and Hostaform® grades with minimal affect on performance properties. It is not meant to be molded as a stand alone product. FDA compliant Hostaform® FK color masterbatches are available in specific colors. Please contact Celanese for details.

Thermal properties	Value	Unit	Test Standard
Melting temperature, 10°C/min	**165**	°C	ISO 11357-1/-3

Typical injection moulding processing conditions

Pre Drying	Value	Unit
Drying time	**3 - 4**	h
Drying temperature	**100 - 120**	°C

Characteristics

Special Characteristics	Auto spec approved
Product Categories	Color concentrate
Delivery Form	Pellets

Other Approvals

OEM	Specification
Bosch	N28 BN90-21-004 (GRAY)
Bosch	N28 BN90-21-008 (BROWN)
Bosch	N28 BN90-21-005 (BROWN)
Bosch	N28 BN90-21-005 (BROWN)

Contact

Americas
8040 Dixie Highway
Florence, KY 41042 USA
Product Information Service
t: +1-800-833-4882
t: +1-859-372-3244
Customer Service
t: +1-800-526-4960
t: +1-859-372-3214
e: info-engineeredmaterials-am@celanese.com

Asia
4560 Jinke Road
Zhang Jiang Hi Tech Park
Shanghai 201210 PRC
Customer Service
t: +86 21 3861 9288
e: info-engineeredmaterials-asia@celanese.com

Europe
Am Unisys-Park 1
65843 Sulzbach, Germany
Product Information Service
t: +49-800-86427-531
t: +49-(0)-69-45009-1011
e: info-engineeredmaterials-eu@celanese.com

General Disclaimer

information contained in this publication should not be construed as a promise or guarantee of specific properties of our products. It is the sole responsibility of the users to investigate whether any existing patents are infringed by the use of the materials mentioned in this publication.Moreover, there is a need to reduce human exposure to many materials to the lowest practical limits in view of possible adverse effects. To the extent that any hazards may have been mentioned in this publication, we neither suggest nor guarantee that such hazards are the only ones that exist. We recommend that persons intending to rely on any recommendation or to use any equipment, processing technique or material mentioned in this publication should satisfy themselves that they can meet all applicable safety and health standards.We strongly recommend that users seek and adhere to the manufacturer's current instructions for handling each material they use, and entrust the handling of such material to adequately trained personnel only. Please call the telephone numbers listed for additional technical information. Call Customer Services for the appropriate Materials Safety Data Sheets (MSDS) before attempting to process our products. The products mentioned herein are not intended for use in medical or dental implants.

Trademark